





Connector for the power supply of Askoll pumps.

TECHNICAL DETAILS

Normative references	EN 61984
Housing type	Free connector, male, non rewirable
Positions	2
Pitch	6 mm
Fastening	By screw
Rated voltage	250 Vac
Rated current, section 0,50 mm2	3A
Frequency	50 / 60 Hz
Rated impulse voltage	2,5 KV (EN 60664-1)
Overvoltage category	II (EN 60664-1)
Pollution degree	2 (EN 60664-1)
Degree of protection IP	N.A. (to test with the opposite part)
Temperature range	-30°C / +90°C
Type of terminals	Female — crimped
Connectable conductors	Flexible cables
Insulation class	II

TEST

Dielectric strenght between live parts and accessible external surface	1500 Vac / 2mA / 60 sec (EN 60512-4-1)
Insula on resistance between live parts and accessible external surface	500 Vdc / 20 MΩ / 60 sec (EN 60512-3-1)
Glow wire test	850°C / 750°C (EN 60335-1)

CABLES

Type	H03V2V2-F / UL Style 2103
------	---------------------------

Section	0,50 mm2 (AWG20)
---------	------------------

MATERIAL MOULDING

External insulation	PVC TM3 / UL 758 105°C
---------------------	------------------------

CATEGORY

Connectors for pumps and circulators

CERTIFICATION

